

TOLERANCES:
Construction tolerances between frames is -0mm +2mm. Frames are manufactured and assembled to +0mm -2mm.

A4

NOTES
THIS DRAWING IS COPYRIGHT: DO NOT SCALE THIS DRAWING, CONTRACTORS MUST CHECK ALL DIMENSIONS ON SITE, ONLY FIGURED DIMENSIONS TO BE WORKED FROM. ALL ERRORS AND DISCREPANCIES MUST BE IMMEDIATELY REPORTED TO THE DESIGN OFFICE OF EOS FRAMING LTD



SINGLE NAILS

COLLATED NAILS (MX)

FIXINGS INTO HOT ROLLED STEEL SUBSTRATE

SUPPLIER REFERENCE:	FIXING LENGTH:	MIN. EDGE DISTANCE:	MIN. FIXING SPACING:	MIN. SUBSTRATE THICKNESS:
HILTI X-U 16 P8 #237330	16mm	20mm	40mm	6mm
HILTI X-U 16 MX #237344	16mm	20mm	40mm	6mm

FIXINGS INTO REINFORCED CONCRETE SLAB SUBSTRATE

SUPPLIER REFERENCE:	FIXING LENGTH:	MIN. EDGE DISTANCE:	MIN. FIXING SPACING:	MIN. SUBSTRATE THICKNESS:
HILTI X-U 27 P8 #237333	27mm	70mm	80mm	80mm
HILTI X-U 27 MX #237347	27mm	70mm	80mm	80mm

IMPORTANT NOTES

1. Fixing quantities and spacings to be determined by EOS Engineer on a job-by-job basis.
2. For fixing into concrete, each piece of track MUST have a minimum of 5 No. fixings.
3. EOS provide fixing specification only – fixings not supplied by EOS.

Title: SHOT FIRED FIXINGS SPECIFICATION (S & T)				STAGE:	
				Preliminary:	<input type="checkbox"/>
				Approval:	<input type="checkbox"/>
				Construction:	<input checked="" type="checkbox"/>
Drawn By: TE	Scale: NTS	Drawing No. 222	Revision: A	Approved By: AH/KB	Date: AUG 2020



EOS Framing Ltd, Hellington Lane, Aycliffe Industrial Park, Newton Aycliffe, County Durham, DL5 6QG, Tel: 01325 303030